



Assembled tables are large & heavy. Put together at place of use.

Natural Stone & Patterned Top Attachment For 5910xx and 5916xx Tables

Thank you for selecting Tropitone furniture.

- ✓ Read through all steps before assembling tables together.
- ✓ Locate all items in the Parts List from your cartons.

WARNING: Do not try to lift or flip furniture with only one person. Furniture pieces may be heavy and awkward to handle, and may result in injury to persons or damage to property if not lifted properly.

WARNING: Do not sit on or put your full weight onto the table. Serious injury could result.

Parts List

Table Top	(4) 5/8" Screws
Table Base	(4) 1/2" Washers
(4) 1/4" Spacers	(4) 1/2" Lock Washers

Tools Required

5/16" Socket Driver or Flathead Screwdriver	Safety Glasses
---	----------------

Natural Stone Tops – Installing a Top

Prepare a smooth, non-scratch work surface (shipping container, a tarp or pool towels can be used). With two persons, place the Table Top upside down on the prepared work surface. With two persons, gently place the Base upside down onto the Top.

Slide a 1/4" spacer between the Top and the Base, aligning the spacer over the screw hole in the base. Place lock washer on screw. Insert screw with lock washer through the corner bracket and spacer into the base. Continue to insert the screw into the threaded insert in the top and hand tighten the screw. DO NOT FULLY TIGHTEN. ALIGNMENT IS COMPLETED AFTER SCREWS ARE LOOSELY INSTALL IN ALL (4) FOUR CORNERS.

Repeat in the remaining three (3) corners

Align the Top and Base.

Fully tighten all four (4) screws. DO NOT OVER TIGHTEN – YOU MAY DAMAGE THE TOP.

With 2 persons, lift the table upright and place in the desired location.

Patterned Aluminum Tops – Replacing a Top

Prepare a smooth, non-scratch work surface (shipping container, a tarp or pool towels can be used). With two persons, place the Table Top upside down on the prepared work surface. With two persons, gently place the Base upside down onto the Top.

Disassemble the Top from the Base by removing four (4) nuts, four (4) lock washers and four (4) 1/4" spacers. Retain for reassembly.

Move Top and Base components off of the prepared work surface.

Place new Top upside down on prepared work surface.

Place a 1/4" spacer on one threaded screw that is welded to each corner of the Top. Repeat for remaining 3 corners.

Place the Base upside down on the Top. Align the mounting holes in the Base to the threaded screws welded to the Top.

Place a lock washer onto the threaded screw. Install a nut on to the threaded screw and hand tighten. DO NOT FULLY TIGHTEN.

ALIGNMENT IS COMPLETED AFTER SCREWS ARE LOOSELY INSTALLED IN ALL (4) FOUR CORNERS

Repeat in remaining three (3) corners.

Align the Top and Base.

Fully tighten all four (4) nuts. DO NOT OVER TIGHTEN – YOU MAY DAMAGE THE TOP.

With 2 persons, lift the table upright and place in the desired location.

Tropitone[®]



MORE INFORMATION

For care and cleaning instructions, refer to the Tropitone Care, Maintenance, Safety & Warranty Information guide included with your furniture and available at www.tropitone.com – click on Product Care.

Additional care information, “How To” videos and assembly instructions for Tropitone Outdoor Furniture and Basta Sole shade products are also available at our website including:

- ✓ Frame Finish Touch Up

If you have difficulty understanding any of the instructions and need assistance, please call Tropitone’s Customer Service Center at 949-951-2010.

Tropitone Furniture Co., Inc.
5 Marconi, Irvine, CA 92618

949 951 2010 phone
www.tropitone.com

Part # R9T00036
Revised: 05-25-17
©2017 Tropitone Furniture Co., Inc.